Jost Chemicals GmbH
Gottlieb Daimler Straße 10
D-69514 Laudenbach/ Germany
Phone: +49 (0) 62 01– 4 28 10
Fax: +49 (0) 62 01– 4 55 90
Email: info@jost-chemicals.de
www: jost-chemicals.de

Geschäftsführer: Manfred Jost
Handelsregister: HRB 431383
USt- IdNr.: DE 215051021

Sealer B-28

SEALER FOR ALL RESIN-TYPES

DESCRIPTION:

Sealer B-28 is a mould sealer for areas of thermoset processing, especially for porous and absorbent mould materials.

APPLICATION:

Sealer B-28 is a mould sealer for the surface sealing of metal, wood and synthetic resin moulds, especially for porous and absorbent mould materials. Weathered and/or slightly damaged synthetic resin or MDF surfaces are sealed smoothly. **Sealer B-28** is a pure sealer and has no release effect.

APPLICATION NOTES:

Sealer B-28 can be applied by using a brush, cotton cloth or a spray-gun.
Brush: Pour the required amount of **Sealer B-28** on the mould and distribute it on the surface in long unidirectional strokes. After a flash-off time of about 10 minutes repeat this procedure. For high-gloss-surfaces it is necessary to sand and polish the first coating before applying the second coating.
Cotton cloth: Pour the required amount of **Sealer B-28** on the mould and distribute it on the surface in a circular motion. After a flash-off time of about 10 minutes repeat this procedure. For high-gloss-surfaces it is necessary to sand and polish the first coating before applying the second coating.

Normally two to three coatings are necessary to seal new moulds.

TECHNICAL DATA:

Sealer B-28 does not provide any demoulding abilities. The use of a release-agent is inevitable. Well-aligned products are for example: ***Mold Sealer S- 31*** or ***Aqua Release 470***.

Shelf life: 12 months after date of production